

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
18 January 2001 (18.01.2001)

PCT

(10) International Publication Number  
WO 01/04375 A1

(51) International Patent Classification<sup>7</sup>: C23C 14/50, (74) Agents: CARTER, Stephen et al.; Mewburn Ellis, York 14/04 House, 23 Kingsway, London WC2B 6HP (GB).

(21) International Application Number: PCT/GB00/02713 (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(22) International Filing Date: 14 July 2000 (14.07.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 9916558.1 14 July 1999 (14.07.1999) GB

(71) Applicant (for all designated States except US): DORMER TOOLS (SHEFFIELD) LIMITED [GB/GB]; Rother Valley Way, Holbrook, Sheffield S20 3RW (GB).

(72) Inventors; and


(75) Inventors/Applicants (for US only): LILL, Richard, Mark [GB/GB]; 18 Woodlands Avenue, Brighton, Sheffield S20 1BP (GB). STEVENSON, Alan [GB/GB]; 14 Collingwood Crescent, Ponteland, Newcastle upon Tyne NE20 9DZ (GB). DICK, John [GB/GB]; 48 Durham Road, Blackhill, Consett, County Durham DH8 8NT (GB).

## Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

## (54) Title: METHOD AND MEANS FOR DRILL PRODUCTION



(57) Abstract: A holder (2; 22; 82) for coating drill with a ceramic coating by a vapour deposition process has a perforated outer wall (4; 24; 84) into which the drills are inserted with their tips projecting. The holder has a hollow interior in which support means locate the inserted drills parallel and with their tips projecting to the same extent. The support means may comprise a correspondingly perforated inner wall (8; 26; 86) and a back wall (10; 28; 88) against which the drills abut, the outer, inner and back walls being parallel to each other. In one configuration, the holder has a hexagonal plan form with alternate outer walls (4) perforated and each with associated inner and back walls (8, 10). The holder is provided with a lid (52) that shields the interior from ingress of the coating material but provides an air passage to assist cooling of the portions of the drills in the holder interior after the coating has been applied.

WO 01/04375 A1

